TC Gard HIGH-PERFORMANCE CHAFE PROTECTION

TC Gard is a tightly braided cover construction of aramid fiber that is spliced onto the strength member to protect it from wear and abrasion in specific areas. Designed for use in regions where extreme heat is an issue, in applications like tug operations, where frequent handling and use put a premium on rope protection and resistance to snagging. For vessels where frequent mooring operations are the norm, TC Gard provides maximum protection for working ropes.

Samson recommends DC Gard (706) made with HMPE fiber if enhanced abrasion resistance is required. If standard abrasion resistance is required, Samson recommends PC Gard (432) made with polyester fiber. Contact Sales Support for more information.

PRODUCT CODE: 707 FIBER: Aramid COLOR: Black

FEATURES:

- > Light and flexible
- > Floats
- > Can be removed for rope inspection
- > Cut resistant
- > Superior durability



INSTALLED ONTO ROPE BODY AND EYES:

SIZE DESIGNATION	FITS ROPE DIAMETER		FITS ROPE CIRCUMFERENCE	
	INCHES	MILLIMETERS	INCHES	MILLIMETERS
Size D	1-5/16" - 1-3/4"	32 - 44 mm	4" - 5-1/2"	96 - 132 mm
Size E	1-7/8" - 2-1/2"	46 - 60 mm	5-5/8" - 7-1/2"	136 - 180 mm

INSTALLED OVER SPLICED AREA:

SIZE DESIGNATION	FITS OVER SPLICED ROPE DIAMETER*		FITS OVER SPLICED ROPE CIRCUMFERENCE*	
	INCHES	MILLIMETERS	INCHES	MILLIMETERS
Size D	3/4" - 1"	18 - 24 mm	2-1/4" - 3"	54 - 72 mm
Size E	1-1/8" - 1-3/8"	28 - 34 mm	3-1/2" - 4-1/8"	84 - 100 mm

*Fits Over Splice specifications refer to the original/base diameter or circumference of the rope used, not the measured dimension of the spliced area.



2090 Thornton Street, Ferndale, WA 98248 USA Tel 01.360.384.4669 | Fax 01.360.384.0572 www.SamsonRope.com